


























# Four Claw Settings

These raw brass cups ideal for use with pointed or shaped back stones.





## Round: (FCR)

						
<b>SS10 RND</b> CB: NR	<b>SS12 RND</b> CB: NR	<b>SS14 RND</b> CB: NR	<b>SS15 RND</b> CB: NR	<b>SS16 RND</b> CB:NR	<b>SS17 RND</b> CB:NR,1R	
						
<b>SS18 RND</b> CB: NR	<b>SS20 RND</b> CB: NR,1R, 1RPB,2R OB: NRSO	<b>SS22 RND</b> CB: NR	<b>SS23 RND</b> CB: NR,1R	<b>SS25 RND</b> CB: NR,1R,2R	<b>SS30 RND</b> CB: NR,1R,1RPB 2R,3R,4R OB:NRSO	
						
<b>SS35 RND</b> CB: NR,1R,2R OB: NRSO,2R	<b>SS36 RND</b> CB: NR	<b>SS38-40</b> OB:4R	<b>SS39 RND</b> CB:1R,2R	<b>SS40 RND</b> CB: NR,1R, 1RPB,2R,3R OB: 4R	<b>SS45 RND</b> CB: NR OB: 4R	<b>SS48 RND</b> CB: NR,2R OB: NRSO
						
<b>SS49 RND</b> CB: NR	<b>SS50 RND</b> CB: NR	<b>SS60 RND</b> CB: 1R,2R,SO	<b>SS75 RND</b> CB: NR	<b>20mm RND</b> CB:NR	<b>27mm RND</b> OB: NR	

## Round Flat Back: takes a 10mm flat back stone.



## Claw: traditional 4 claw setting. Available with or without a b suitable for soldering.

6mm:			8mm:		
	<b>FC06</b> - without soldering pad-			<b>FC08</b>	
	<b>FC06P</b> - with soldering pad-			<b>FC08P</b>	

Note: CB = Closed Back, OB = Open Back, SB = Shaped Back, PB = Pointy Back, FB = Flat Back, RV = Rivet Back, RL = Rivoli, BB = Button Back, SO = Sew On, CC = Corner Claw, PE = Plain Edge, D = Deep Cup, NR = No Ring, 1R = 1 Ring, 2R = 2 Ring, 3R = 3 Ring, 4R = 4 Ring

0 10 20 30 40 50mm